

GIORGIO GRAESAN and Friends	TECHNICAL SHEET PRIMUS SABBIA	Code	TDS1031_00
		Revision	00
		Date	28/06/2018

1. DESCRIPTION

PRIMUS SABBIA is a water-based insulating acrylic primer, designed to provide the ideal substrate for all acrylic finishes applied with glove or brush. This product is solvent-free and has a low organic compound content.

2. USE

PRIMUS SABBIA can be applied on setting coats, skimming coats and plasterboards.

3. PREPARING THE SUBSTRATE

Proper preparation of the substrate is essential for a perfect finish. Therefore, eliminate any peeling or crumbling paint or plaster, taking care to wash or brush any mould or dust. Before applying PRIMUS SABBIA, the surface must always be properly cohesive, otherwise, proceed with an insulating bonding agent, recommended especially in the case of plasterboard walls.

In the case of walls finished with lime-based products and treated with wax or soap, we recommend sanding and removing the dust before applying PRIMUS SABBIA.

Next, apply PRIMUS SABBIA.

4. METHOD OF APPLICATION

This product is ready for use; however, we recommend mixing it before applying it with a roller.

Apply one coat of PRIMUS SABBIA and wait 24 hours before proceeding with the next application of lime-based products.

5. CLEANING THE TOOLS

Clean the tools with water immediately after use.

6. SAFETY RECOMMENDATIONS AND RISK IDENTIFICATION.

The product does not require labelling according to current regulations. Use the product according to current health and safety regulations; after use, do not dispose of containers to the environment; let residue dry thoroughly and handle as special waste. Keep out of the reach of children. If swallowed, seek medical advice immediately and show this container or label. Do not empty into drains, waterways or soil.

For more information, see safety data sheet available on: www.giorgiograesan.it

GIORGIO GRAESAN and Friends	TECHNICAL SHEET	Code	TDS1031_00
	PRIMUS SABBIA	Revision	00
		Date	28/06/2018

TECHNICAL CHARACTERISTICS: APPLICATION	
Dilution	Product is ready for use.
Mixing	Always mix before use
Colouring	Not provided
Tools	Roller
Primer	Not provided
Conditions of application	From +10°C to +35°C with relative humidity < 85%
Number of coats	1
Drying time	4-6 hours at 20°C
Curing time	24 hours at 20°C

TECHNICAL CHARACTERISTICS: COVERAGE	
PRIMUS SABBIA	6 – 7 sqm/litre

TECHNICAL CHARACTERISTICS: PRODUCT	
Composition	Acrylic copolymer in water emulsion, additives, mineral fillers
Specific weight	1.56 ± 0.03 kg/litre
pH	>8.0 - 8.5
EU limit value (Directive 2004/42/EC) Cat. A/g: primer (water-borne): 30 g/l	Maximum VOC content 1.79 g/l
Storage conditions	Keep in tightly sealed container, even after use and after cleaning the sides and lid of the tin, in a cool, dry place at temperatures between +5°C and +30°C
Packaging	1 – 2.5 – 5 – 15 litres

Giorgio Graesan & Friends guarantees that the information in this sheet is provided to the best of its experience and its technical and scientific knowledge, however cannot assume any responsibility for the results obtained with their use as the conditions of application are beyond its control. We recommend always checking the actual suitability of the product for each specific case. This sheet nullifies and replaces any previous version. For more information, call phone number **(+39) 02.9903951** or on **Whatsapp: (+39) 3371410335**.